

TS-600

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-600	3.00-10	2.15×10	32J	80/3.15	413/16.3	112/245	TT/TL
		2.15×10	4PR	80/3.15	413/16.3	150/330	TT/TL
		2.15×10	6PR	80/3.15	413/16.3	175/385	TT/TL
		2.15×10	8PR	80/3.15	413/16.3	185/410	TT/TL
	3.50-10	2.50x10	4PR	92/3.62	437/17.2	195/430	TT/TL
		2.50x10	6PR	92/3.62	437/17.2	224/495	TT/TL
		2.50x10	8PR	92/3.62	437/17.2	236/520	TT/TL
	90/90-10	2.15x10	41J	90/3.54	416/16.4	145/320	TT/TL
		2.15x10	50J	90/3.54	416/16.4	190/420	TT/TL
		2.15x10	55J	90/3.54	416/16.4	218/480	TT/TL
	100/90-10	2.50×10	46J	101/3.98	434/17.1	170/375	TT/TL
		2.50×10	56J	101/3.98	434/17.1	224/495	TT/TL
		2.50×10	61J	101/3.98	434/17.1	257/565	TT/TL
	80/100-10	1.85×10	38J	80/3.15	414/16.3	132/290	TT/TL
		1.85×10	46J	80/3.15	414/16.3	170/375	TT/TL
		1.85×10	52J	80/3.15	414/16.3	200/440	TT/TL
	80/90-10	1.85×10	35J	80/3.15	398/15.7	121/265	TT/TL
		1.85×10	44J	80/3.15	398/15.7	160/350	TT/TL
		1.85×10	49J	80/3.15	398/15.7	185/410	TT/TL
	90/90-12	2.15×12	44J	90/3.54	467/18.4	160/355	TT/TL
		2.15×12	54J	90/3.54	467/18.4	212/470	TT/TL
		2.15×12	59J	90/3.54	467/18.4	243/535	TT/TL

TS-601

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-601	3.5-10	2.50×10	4PR	92/3.62	437/17.2	195/430	TT/TL
		2.50×10	6PR	80/3.15	413/16.3	150/330	TT/TL
		2.50×10	8PR	80/3.15	413/16.3	175/385	TT/TL
	90/90-10	2.15×10	41J	90/3.54	416/16.4	145/320	TL

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
		2.15×10	50J	90/3.54	416/16.4	190/420	TL
		2.15×10	55J	90/3.54	416/16.4	218/480	TL
		2.15×10	56J	90/3.54	416/16.4	224/495	TL

TS-602

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-602	70/90-17	1.60×17	38N	69/2.72	558/22.0	132/290	TL
		1.60×17	43N	69/2.72	558/22.0	155/340	TL
	80/90-14	1.85×14	40N	80/3.15	500/19.7	140/310	TL
	80/90-16	1.85×16	43N	80/3.15	550/21.7	155/340	TL
		1.85×16	48N	80/3.15	550/21.7	180/395	TL
	80/90-17	1.85×17	44N	80/3.15	576/22.7	160/355	TL
		1.85×17	50N	80/3.15	576/22.7	190/420	TL

TS-603

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-603	3.00-10	2.15×10	32J	80/3.15	413/16.3	112/245	TT/TL
		2.15×10	6PR	80/3.15	413/16.3	175/385	TT/TL
		2.15×10	8PR	80/3.15	413/16.3	185/410	TT/TL

TS-606

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-606	120/70-12	3.50×12	51J	122/4.80	473/18.6	195/430	TL
		3.50×12	58J	122/4.80	473/18.6	236/520	TL
	130/60-13	3.50×13	53J	129/5.08	486/19.1	206/455	TL
		3.50×13	60J	129/5.08	486/19.1	250/550	TL
	130/70-12	3.50×12	56N	129/5.08	487/19.2	224/495	TL
		3.50×12	62N	129/5.08	487/19.2	265/585	TL

TS-607

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-607	2.50-17	1.60×17	4PR	65/2.56	568/22.4	132/290	TT
		1.60×17	6PR	65/2.56	568/22.4	155/340	TT
		1.60×17	8PR	65/2.56	568/22.4	165/365	TT
	2.75-17	1.85×17	4PR	75/2.95	588/23.1	145/320	TT
		1.85×17	6PR	75/2.95	588/23.1	175/385	TT
		1.85×17	8PR	75/2.95	588/23.1	190/420	TT
	3.00-17	1.85×17	4PR	80/3.15	602/23.7	165/365	TT
		1.85×17	6PR	80/3.15	602/23.7	190/420	TT
		1.85×17	8PR	80/3.15	602/23.7	206/455	TT

TS-607

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-607	2.50-17	1.60×17	4PR	65/2.56	568/22.4	132/290	TT
		1.60×17	6PR	65/2.56	568/22.4	155/340	TT
		1.60×17	8PR	65/2.56	568/22.4	165/365	TT
	2.75-17	1.85×17	4PR	75/2.95	588/23.1	145/320	TT
		1.85×17	6PR	75/2.95	588/23.1	175/385	TT
		1.85×17	8PR	75/2.95	588/23.1	190/420	TT
	3.00-17	1.85×17	4PR	80/3.15	602/23.7	165/365	TT
		1.85×17	6PR	80/3.15	602/23.7	190/420	TT
		1.85×17	8PR	80/3.15	602/23.7	206/455	TT

TS-611

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-611	3.25-16	2.15×16	4PR	89/3.50	588/23.1	180/395	TT
		2.15×16	6PR	89/3.50	588/23.1	218/480	TT
		2.15×16	8PR	89/3.50	588/23.1	236/520	TT

TS-612

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-612	3.25-18	2.15×18	4PR	89/3.50	639/25.2	200/440	TT/TL
		2.15×18	6PR	89/3.50	639/25.2	243/535	TT/TL
		2.15×18	8PR	89/3.50	639/25.2	265/585	TT/TL

TS-613F

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-613F	110/70H17	3.00×17	54H	110/4.33	586/23.1	212/470	TT/TL

TS-613R

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-613R	140/70H17	3.75×17	66H	139/5.47	628/24.7	300/660	TT/TL
		3.75×17	72H	139/5.47	628/24.7	335/740	TT/TL

TS-615

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-615	2.75-18	1.85×18	4PR	75/2.95	613/24.1	150/330	TT
		1.85×18	6PR	75/2.95	613/24.1	180/395	TT
	2.50-17	1.60×17	4PR	65/2.56	568/22.4	132/290	TT
		1.60×17	6PR	65/2.56	568/22.4	155/340	TT
	2.50-18	1.60×18	4PR	65/2.56	593/23.3	140/310	TT
		1.60×18	6PR	65/2.56	593/23.3	165/365	TT
		1.60×18	8PR	65/2.56	593/23.3	175/385	TT

TS-616

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-616	2.25-17	1.60×17	4PR	61/2.40	556/21.9	115/255	TT
		1.60×17	6PR	61/2.40	556/21.9	132/290	TT
	2.75-14	1.85×14	4PR	75/2.95	512/20.2	121/265	TT

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
		1.85×14	6PR	75/2.95	512/20.2	145/320	TT
		1.85×14	8PR	75/2.95	512/20.2	160/350	TT

TS-617

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-617	3.00-18	1.85×18	4PR	80/3.15	627/24.7	175/385	TT
		1.85×18	6PR	80/3.15	627/24.7	200/440	TT
		1.85×18	8PR	80/3.15	627/24.7	218/480	TT

TS-618

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-618	3.25-18	2.15×18	4PR	89/3.50	639/25.2	200/440	TT/TL
		2.15×18	6PR	89/3.50	639/25.2	243/535	TT/TL
		2.15×18	8PR	89/3.50	639/25.2	265/585	TT/TL

TS-619

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-619	3.50-16	2.15×16	4PR	93/3.66	598/23.5	200/440	TT/TL
		2.15×16	6PR	93/3.66	598/23.5	236/520	TT/TL
		2.15×16	8PR	93/3.66	598/23.5	257/565	TT/TL

TS-620

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-620	3.00-18	1.85×18	4PR	80/3.15	627/24.7	175/385	TT/TL
		1.85×18	6PR	80/3.15	627/24.7	200/440	TT/TL
		1.85×18	8PR	80/3.15	627/24.7	218/480	TT/TL

TS-621

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-621	3.00-10	2.15×10	32J	80/3.15	413/16.3	112/245	TT/TL
		2.15×10	4PR	80/3.15	413/16.3	150/330	TT/TL
		2.15×10	6PR	80/3.15	413/16.3	175/385	TT/TL
		2.15×10	8PR	80/3.15	413/16.3	185/410	TT/TL

TS-622

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-622	3.50-10	2.50×10	4PR	92/3.62	437/17.2	195/430	TT/TL
		2.50×10	6PR	92/3.62	437/17.2	224/495	TT/TL
		2.50×10	8PR	92/3.62	437/17.2	236/520	TT/TL
	2.75-14	1.85×14	4PR	75/2.95	512/20.2	121/265	TT
		1.85×14	6PR	75/2.95	512/20.2	145/320	TT
		1.85×14	8PR	75/2.95	512/20.2	160/350	TT
	2.50-14	1.60×14	4PR	65/2.56	492/19.4	112/245	TT
		1.60×14	6PR	65/2.56	492/19.4	128/280	TT

TS-623

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-623	2.75-18	1.85×18	4PR	75/2.95	613/24.1	150/330	TT/TL
		1.85×18	6PR	75/2.95	613/24.1	180/395	TT/TL
		1.85×18	8PR	75/2.95	613/24.1	195/430	TT/TL

TS-625

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-625	90/90-10	2.15×10	41J	90/3.54	416/16.4	145/320	TT/TL
		2.15×10	50J	90/3.54	416/16.4	190/420	TT/TL
		2.15×10	55J	90/3.54	416/16.4	218/480	TT/TL
		2.15×10	56J	90/3.54	416/16.4	224/495	TT/TL

TS-626

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-626	110/70-12	3.00×12	47N	110/4.33	459/18.1	175/385	TL

TS-627

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-627	2.75-17	1.85×17	4PR	75/2.95	588/23.1	145/320	TT
		1.85×17	6PR	75/2.95	588/23.1	175/385	TT
		1.85×17	8PR	75/2.95	588/23.1	190/420	TT

TS-628

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-628	3.00-17	1.85×17	4PR	80/3.15	602/23.7	165/365	TT
		1.85×17	6PR	80/3.15	602/23.7	190/420	TT
		1.85×17	8PR	80/3.15	602/23.7	206/455	TT

TS-631

Tread No.	Size	Rim (inch)	Ply Rating	S.W. (mm/inch)	O.D. (mm/inch)	Maximum Load Capacity (kg/lbs)	TT/TL
TS-628	100/60-12	2.75×12	39J	100/3.94	425/16.7	136/300	TL
		2.75×12	45J	100/3.94	425/16.7	165/365	TL
	80/60-10	1.85×10	31J	80/3.94	382/15.0	109/240	TL
		1.85×10	41J	80/3.94	382/15.0	145/320	TL
		1.85×10	46J	80/3.94	382/15.0	170/375	TL